SUBDIVISION OF SECTION 33, T. 20 N., R. 31 E., MOUNT DIABLO MERIDIAN, NEVADA

	1. Zo W., R. Si E., MOONI BIIDDO MERIDIIM, MUVIDII
CHAINS	N. 0°22'40" W., on the N-S center line of the SW1/4 of sec. 33.
19.864	Point for the SW $1/16$ sec. cor. of sec. 33, at intersection with the E-W center line of the SW1/4.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	SW 1/16 S33
	2006
36.645	Point for a witness point, determined at 200 ft. dist. from the C-W 1/16 sec. cor. of sec. 33.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	WP W
	s — 33
	S 33 W
	···
20 676	2006
39.676	The C-W 1/16 sec. cor. of sec. 33.
	From the point for the C-S 1/16 sec. cor. of sec. 33.
	N. 89°47'20" W., on the E-W center line of the SW1/4 of sec. 33.
19.43	Improved gravel road, bears N. and S.
20.133	The SW 1/16 sec. cor. of sec. 33.
40.208	The point for S 1/16 sec. cor. of secs. 32 and 33.
	MERCIA AND DOLLARD GUIDANNA ENDOUGH
	METES-AND-BOUNDS SURVEY THROUGH SECTIONS 14, 22, 23, 27, 28 AND 33,
	T. 20 N., R. 31 E., MOUNT DIABLO MERIDIAN, NEVADA
	From the witness point on the N-S center line of the SW1/4 of sec. 33, hereinbefore described.
	S. 89°57'40" E., on a line parallel to the E-W center line of sec. 33.
6.471	Point for Angle Point No. 1, sec. 33, at intersection with a line 30 ft. westerly and perpendicular to the apparent centerline of the existing improved gravel road.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet with brass cap mkd.