

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 17 S., R. 50 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS									
	<p>Reestablishment of a Portion of the Survey Executed by E.A. Carter, U.S. Deputy Surveyor, in 1881, and a Portion of the Dependent Resurvey Executed by H.G. Parker, Cadastral Surveyor, in 1963</p> <hr/> <p>From the 1/4 sec. cor. of secs. 11 and 12, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the subdivisional lines of T. 17 S., R. 50 E., executed under Group No. 408, with a mound of stone 2 ft. diam., 1/2 ft. high, W. of cor.</p> <p>N. 3°53'20" W., bet. secs. 11 and 12.</p> <p>Over gently rolling land.</p>								
37.808	<p>The cor. of secs. 1, 2, 11 and 12, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the subdivisional lines of T. 17 S., R. 50 E., executed under Group No. 408, with a mound of stone, 2 1/2 ft. diam., 1 ft. high, W. of cor.</p> <hr/> <p>From the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the Tp., hereinbefore described.</p> <p>N. 88°54'40" W., bet. secs. 1 and 12.</p> <p>Over gently rolling land.</p>								
20.045	<p>The E 1/16 sec. cor. of secs. 1 and 12, determined by Richard L. Hafen, Nevada Professional Land Surveyor No. 4428, monumented with a rebar, 5/8 in. diam., 18 ins. long, firmly set flush with the ground, with aluminum cap mkd. RL HAFEN RLS 4428. This monument is locally recognized as the position of the corner point and is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr> <td></td> <td style="text-align: center;">S 1</td> </tr> <tr> <td style="text-align: center;">E 1/16</td> <td style="text-align: center;">—</td> </tr> <tr> <td></td> <td style="text-align: center;">S12</td> </tr> <tr> <td></td> <td style="text-align: center;">2006</td> </tr> </table> </div> <p>Insert the rebar inside the stainless steel post, and set a steel boundary post, 8 ft. long, alongside the stainless steel post.</p> <hr/> <p>N. 88°54'40" W., beginning new measurement.</p>		S 1	E 1/16	—		S12		2006
	S 1								
E 1/16	—								
	S12								
	2006								