SUBDIVISION OF SECTION 19, T. 17 S., R. 50 E., MOUNT DIABLO MERIDIAN, NEVADA

T. 17 S., R. 50 E., MOUNT DIABLO MERIDIAN, NEVADA
Point for the center $1/4$ sec. cor. of sec. 19, at intersection with the E-W center line.
Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, 1 ft. diam., with brass cap mkd.
T17S R50E
C 1/4 S19
2006
Mine haul road, bears NE. and SW.
The 1/4 sec. cor. of secs. 18 and 19, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the subdivisional lines of T. 17 S., R. 50 E., executed under Group No. 408, with a mound of stone, 2 ft. diam., W. of cor.
From the 1/4 sec. cor. of secs. 19 and 20.
S. 88°44'20" W., on the E-W center line of sec. 19.
Over rolling land.
Fence, bears NE. and SW.
Point for the center E 1/16 sec. cor. of sec. 19.
POINT NOT MONUMENTED.
The center 1/4 sec. cor. of sec. 19.
Mine haul road, bears NE. and SW.
The 1/4 sec. cor. of secs. 19 and 24, on the W. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the west boundary of T. 17 S., R. 50 E., executed under Group No. 408, with a carsonite post firmly set alongside, projecting 4 ft. above the ground.
From the E 1/16 sec. cor. of secs. 19 and 30.
N. 2°58'10" W., on the N-S center line of the SE1/4 of sec. 19.
Along fence, over rolling land.
The SE 1/16 sec. cor. of sec. 19, determined by U.S. Fish and Wildlife Service, monumented with a rebar, 3/4 in. diam., 30 ins. long, firmly set, projecting 4 ins. above the ground, with aluminum cap mkd. SE 1/16 S19 1987. This monument is locally recognized as the position of the corner point, and is accepted as a careful and faithful determination of the position of the corner.