

DEPENDENT RESURVEY OF THE SECOND STANDARD PARALLEL NORTH,
THROUGH A PORTION OF RANGE 22 EAST,
MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>Reestablishment of a Portion of the Survey Executed by B. Ives, U.S. Deputy Surveyor, in 1861, and a Portion of the Dependent Resurvey Executed by C.S. Swanholm, Cadastral Engineer, in 1940-45</p> <hr/> <p>Beginning at the standard cor. of Tps. 11 N., Rs. 22 and 23 E., monumented with an iron post, 3 ins. diam., firmly set, projecting 18 ins. above the ground, supported in a mound of stone, 4 ft. base, to top, with brass cap mkd. as described in the field notes of the dependent resurvey of the Second Standard Parallel North through Range 22 East, executed under Group No. 246. During the course of this survey, this monument was removed by person(s) unknown.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a mound of stone, 4 ft. base, to top, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">SC T11N R22E R23E S36 S31</p> <hr style="width: 10%; margin: auto;"/> <p style="text-align: center;">2007</p> <p>Cor. is located 20 lks. W. of a jeep trail, 20 lks wide, extending SE. and NW.</p> <p>S. 89°56'30" W., on the S. bdy. of sec. 36.</p> <p>Over low hills covered with sagebrush and scattered pinon pines.</p> <p>12.684 The closing cor. of Tps. 10 N., Rs. 22 and 23 E., hereinafter described.</p> <p>32.311 Point for the E 1/16 sec. cor. of sec. 1 only, T. 10 N., R. 22 E., hereinafter described.</p> <p>40.065 The standard 1/4 sec. cor. of sec. 36, monumented with an iron post, 2 ins. diam., firmly set, projecting 18 ins. above the ground, supported in a mound of stone, 4 ft. base, to top, with brass cap mkd. as described in the field notes of the dependent resurvey of the Second Standard Parallel North through Range 22 East, executed under Group No. 246, from which the 1940-45 bearing trees</p> <p style="padding-left: 40px;">A pinon pine, 25 ins. diam., bears N. 9° E., 65.0 lks. dist., with the marks S1/4 BT visible.</p> <p style="padding-left: 40px;">A pinon pine, 20 ins. diam., bears N. 43 3/4° W., 90.0 lks. dist., with the marks 1/4 SC BT visible.</p> <hr/>