

DEPENDENT RESURVEY OF A PORTION OF
THE SUBDIVISION-OF-SECTION LINES OF SECTION 6,
T. 12 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p style="text-align: center;">Reestablishment of a Portion of the Subdivision of Section 6, Executed by J.A. Mack in 1986-87</p> <hr/>
	<p>From the E 1/16 sec. cor. of secs. 6 and 7, monumented with an aluminum post, 2 1/2 ins. diam., projecting 5 ins. above the ground with aluminum cap mkd. as described in the field notes of the dependent resurvey of T. 12 N., R. 29 E., executed under Group No. 635, with a mound of stone, 2 1/2 ft. base, 1 ft. high, N. of the cor.</p> <p>N. 0°03'30" W., on the N-S center line of the SE1/4 of sec. 6.</p> <p>Across rolling land, through scattered cottonwoods, willows and tamarisk.</p>
9.90	Descend into river cut, bears NW. and SE.
19.00	Right bank of the Walker River, bears NW. and SE., thence across river course SE.
19.972	True point for the SE 1/16 sec. cor. of sec. 6, at intersection with the E-W center line of the SE1/4, falls in the Walker River where it is impractical to set a permanent monument.
20.50	Left bank of the Walker River, bears SE. and NW.
20.60	Leave river cut, bears NW. and SE., continue across nearly level land, covered with scattered sagebrush and grasses.
21.995	<p>Point selected for the witness SE 1/16 sec. cor. of sec. 6.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">WC SE 1/16 S 6 2006 ↓</p>
22.436	Record distance for the 1986-87 witness SE 1/16 sec. cor. of sec. 6, there is no evidence remaining of the monument set in 1986-87.
39.946	<p>The C-E 1/16 sec. cor. of sec. 6, monumented with an aluminum post, 2 1/2 ins. diam., 12 ins. below the surface of the ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of T. 12 N., R. 29 E., executed under Group No. 635.</p> <hr/> <p>From the C-E-SE 1/64 sec. cor. of sec. 6, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 10 ins. above the ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of T. 12 N., R. 29 E., executed under Group No. 635.</p>