

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 16 N., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>Reestablishment of a Portion of the Survey Executed by E.B. Monroe and A.G. Bateman, U.S. Deputy Surveyors, in 1872, and a Portion of the Dependent Resurvey by H.G. Parker and R.A. Pratt, Cadastral Surveyors, in 1967</p> <hr/>
	<p>Beginning at the 1/4 sec. cor. of secs. 35 and 36, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above the ground, in a collar of stone, 2 ft. base, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 16 N., R. 63 E., executed under Group No. 446, with a steel fence post, projecting 3 1/2 ft. above the ground, SE. of cor.</p>
	<p>N. 0°13'30" W., bet. secs. 35 and 36.</p>
	<p>Across gentle NE. slope, through scattered undergrowth.</p>
1.515	<p>Point for a witness point at the intersection of a line parallel to and 100 ft. northerly of the E-W center line of sec. 35 with the line bet. secs. 35 and 36, hereinafter described. The monument for this witness point also occupies the position for a witness point at the intersection of a line parallel to and 100 ft. northerly of the E-W center line of sec. 36 with the line bet. secs. 35 and 36, also hereinafter described.</p>
19.797	<p>The N 1/16 sec. cor. of secs. 35 and 36, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 10 ins. above the ground, in a collar of stone, 2 ft. base, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 16 N., R. 63 E., executed under Group No. 446.</p> <hr/>
	<p>From the 1/4 sec. cor. of secs. 34 and 35, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 12 ins. above the ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 16 N., R. 63 E., executed under Group No. 446.</p> <p>N. 0°23'20" W., bet. secs. 34 and 35.</p> <p>Across gentle NE. slope, through scattered juniper and undergrowth.</p>
1.515	<p>Point for a witness point at the intersection of a line parallel to and 100 ft. northerly of the E-W center line of sec. 34, with the line bet. secs. 34 and 35, hereinafter described. The monument for this witness point also occupies the position for a witness point at the intersection of a line parallel to and 100 ft. northerly of the E-W center line of sec. 35, with the line bet. secs. 34 and 35, also hereinafter described.</p>
19.696	<p>The N 1/16 sec. cor. of secs. 34 and 35, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 12 ins. above the ground, in a mound of stone, 5 ft. base, 1/2 ft. high, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 16 N., R. 63 E., executed under Group No. 446, with a steel fence post, projecting 4 ft. above the ground, W. of cor.</p> <hr/>