

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 16 N., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>S27 E-E 1/64 S34 2007</p>
	<p>Set a steel sign post alongside the stainless steel post.</p>
20.124	<p>The E 1/16 sec. cor. of secs. 27 and 34, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 11 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 16 N., R. 63 E., executed under Group No. 446, with a mound of stone, 2 1/2 ft. base, 1/2 ft. high, N. of cor.</p>
	<hr/> <p style="text-align: center;">SUBDIVISION OF SECTION 25, T. 16 N., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/>
	<p>From the 1/4 sec. cor. of secs. 25 and 36, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 16 N., R. 63 E., executed under Group No. 446, with a mound of stone, 2 ft. base, 1 ft. high, N. of cor.</p>
	<p>N. 0°34'40" W., on the N-S center line of sec. 25.</p>
	<p>Across rolling land, through scattered undergrowth.</p>
12.90	<p>Center of graded dirt road, 15 lks. wide, bears NW. and SE.</p>
15.41	<p>From this point, the cor. of barbed wire fences extending N. and SE. bears E., 0.21 chs. dist. Continue along fence line.</p>
19.922	<p>Point for the C-S 1/16 sec. cor. of sec. 25. POINT NOT MONUMENTED</p>
28.19	<p>From this point, the cor. of barbed wire fences extending NW. and S. bears W., 0.05 chs. dist. Leave fence line and continue along W. side of level grasslands.</p>
39.844	<p>Point for the center 1/4 sec. cor. of sec. 25, at intersection with the E-W center line. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p style="text-align: center;">T16N R63E C 1/4 S25 2007</p>
	<p>Set a steel sign post alongside the stainless steel post.</p>