

SUBDIVISION OF SECTION 25,
T. 16 N., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
79.696	<p>The 1/4 sec. cor. of secs. 24 and 25, monumented with an iron post, 28 ins. long, 2 1/2 ins. diam., loosely set flush with the surface of the ground, leaning at an angle, in a submerged stone base, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 16 N., R. 63 E., executed under Group No. 446. Accepted base of iron post as the best available evidence of the position of the 1967 corner.</p> <p>At the corner point</p> <p>Reset the iron post 26 ins. in the ground, over a plastic-encased magnet, and in a supporting collar of stone, 2 ft. base, submerged below the surface of the ground. Add the marks 2007 to the brass cap.</p> <p>Set a steel fence post alongside the stainless steel post.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 25 and 30, on the E. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 3 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the E. bdy. of T. 16 N., R. 63 E., executed under Group No. 446.</p> <p>S. 89°21'10" W., on the E-W center line of sec. 25.</p> <p>Across open grassland.</p>
38.90	<p>Irrigation ditch, 10 lks. wide, 2 ft. deep, drains NE.</p> <p>Enter scattered undergrowth and ascend gentle E. slope.</p>
40.637	The center 1/4 sec. cor. of sec. 25.
45.17	Barbed wire fence, bears NW. and SE.
46.65	Center of dirt road, 15 lks. wide, parallels fence line.
60.703	<p>Point for the C-W 1/16 sec. cor. of sec. 25.</p> <p>POINT NOT MONUMENTED</p>
80.769	<p>The 1/4 sec. cor. of secs. 25 and 26, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 9 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 16 N., R. 63 E., executed under Group No. 446, with a mound of stone, 3 ft. base, 1 ft. high, W. of cor.</p> <hr/> <p>From the W 1/16 sec. cor. of secs. 25 and 36, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 7 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 16 N., R. 63 E., executed under Group No. 446, with a mound of stone, 3 ft. base, 1/2 ft. high, N. of cor.</p> <p>N. 0°28'00" W., on the N-S center line of the SW1/4 of sec. 25.</p>