

METES-AND-BOUNDS SURVEY IN SECTION 35,  
T. 16 N., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the point for a witness point at the intersection of a line parallel to and 100 ft. northerly of the E-W center line of sec. 35, with the line bet. secs. 35 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>WP T16N R63E S   S --- ---</p> <p>35   36</p> <p>2007</p> </div> <p>Set a steel sign post alongside the stainless steel post.</p> <p>This monument occupies the position of the intersection of a line parallel to and 100 ft. northerly of the E-W center line of sec. 36 with the line bet. secs. 35 and 36, hereinafter described.</p> <p>S. 89°50'50" W., on a line parallel to and 100 ft. northerly of the E-W center line of sec. 35.</p> <p>Across rolling land, sagebrush and bunchgrass.</p>
28.989	<p>Point for a witness point at the intersection of a line parallel to and 100 ft. northerly of the E-W center line of sec. 35, with the centerline of U.S. Highway Nos. 6, 50 and 93.</p> <p>Set a PK nail flush with the asphalt surface.</p> <p>from which</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears N. 25°22' E., 122.7 lks. dist., with brass cap mkd. RM WP S35 81.0 FT TO COR 2007 and an arrow pointing to the cor. Set a steel sign post alongside the stainless steel post.</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears N. 75°21' E., 167.7 lks. dist., with brass cap mkd. RM WP S35 110.7 FT TO COR 2007 and an arrow pointing to the cor. Set a steel sign post alongside the stainless steel post.</p> <hr style="width: 60%; margin-left: 0;"/> <p>From the point for a witness point at intersection with a line parallel to and 100 ft. northerly of the E-W center line of sec. 35, with the N-S center line of the SW1/4 of the NW1/4 of sec. 35.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>