

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 20 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground to solid rock, over a plastic-encased magnet, and in a mound of stone, 2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">S 1/16 S11 S12</p> <p style="text-align: center;">2007</p> <p>From this corner, a rebar, 5/8 in. diam., firmly set flush with the ground, with a 1 1/4 in. diam. red plastic cap mkd. WLB PLS 3951, bears N. 69° E., 0.014 chs. dist. established by Clark G. Post, Nevada Professional Land Surveyor No. 3951, using incorrect procedures, as shown on Clark County, Nevada, File 147, Page 54 of Surveys and was not utilized during the course of this survey.</p> <hr/> <p>N. 0°57'20" W., beginning new measurement.</p> <p>Continue over gently rolling desert valley.</p> <p>1.91 Base of steep rocky SE. slope; asc. over broken SE. and E. slope.</p> <p>19.137 The 1/4 sec. cor. of secs. 11 and 12, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 9 ins. above a mound of stone, 4 ft. diam., 2 1/2 ft. high, mkd. as described in the field notes of the dependent resurvey of a portion of the subdivisional lines of T. 20 S., R. 59 E., executed under Group No. 362.</p> <hr/> <p style="text-align: center;">DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISION-OF-SECTION LINES OF SECTION 12, T. 20 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p style="text-align: center;">Reestablishment of a Portion of the Survey Executed by Cadastral Surveyor P.K. Russell in 1957</p> <hr/> <p>From the C-W 1/16 sec. cor. of sec. 12, reestablished and recorded by numerous Professional Land Surveyors and most recently reestablished by Michael G. Smith, Nevada Professional Land Surveyor No. 16201, in 2006, monumented with a brass disc, 2 ins. diam., set flush with the asphalt surface, mkd. W1/16 C--C 12 PLS 16201, per unrecorded Monument Tie Map of Sierra 2 Unit 1. This is accepted as a careful and faithful reestablishment of the position of the corner determined in 1957.</p> <p>from which accessories established by Michael G. Smith</p> <p style="padding-left: 40px;">An aluminum cap, 1 1/2 ins. diam., firmly set in top of concrete curb, mkd. 69.39 RM MSG PLS 16201, bears N. 64°57' E., 105.1 lks. dist.</p> <p style="padding-left: 40px;">An aluminum cap, 1 1/2 ins. diam., firmly set in top of concrete curb, mkd. 69.51 80.04 RM MSG PLS 16201, bears S. 61°21' E., 105.3 lks. dist.</p>
--------	--