

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,
T. 12 S., R. 47 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From this corner, a rebar, determined to be a reference monument to the original cor., set by Lisle Lowe, Nevada Professional Land Surveyor No. 8423, 1/2 in. diam., firmly set, projecting 4 ins. above the ground, with plastic cap mkd. PLS 8423 as recorded in Nye County, Nevada, Record of Survey, File No. 411077, bears NORTH, 0.010 chs. dist.</p> <hr/> <p>N. 0°04'40" E., beginning new measurement.</p> <p>10.00 Dry wash, 50 lks. wide, drains SE.</p> <p>16.45 Powerline, bears N. 35° W. and S. 35° E.</p> <p>26.00 Gravel road, 40 lks. wide, bears N. 23° W. and S. 23° E.</p> <p>40.072 The cor. of Tps. 11 and 12 S., Rs. 46 and 47 E., monumented with a basalt stone, 21x14x10 ins., firmly set, projecting 12 ins. above the ground, plainly mkd. with 6 notches on the N., S., E. and W. edges, T 11 S on NE. face, R 47 E on SE. face, T 12 S on SW. face and R 46 E on NW. face, and a mound of stone, 3 ft. base, 1 ft. high, S. of the cor., with a rebar determined to be a reference monument to the original cor., set by Lisle Lowe, Nevada Professional Land Surveyor No. 8423, 1/2 in. diam., firmly set alongside the original cornerstone, projecting 6 ins. above the ground, with plastic cap mkd. PLS 8423, as recorded in Nye County, Nevada, Record of Survey, File No. 411077.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <table> <tr><td>T11S</td><td></td></tr> <tr><td>R46E</td><td>R47E</td></tr> <tr><td>S36</td><td>S31</td></tr> <tr><td>S 1</td><td>S 6</td></tr> <tr><td>T12S</td><td></td></tr> </table> <p>2007</p> </div> <p>Deposit the original cornerstone, and reset the rebar alongside the stainless steel post.</p> <hr/> <p>DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY, T. 12 S., R. 47 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>Reestablishment of a Portion of the Survey Executed by O.E. Brashears, U.S. Deputy Surveyor, in 1906</p> <hr/> <p>From the cor. of secs. 5, 6, 31 and 32, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the south boundary of T. 11 S., R. 47 E., executed under Group No. 772, with a mound of stone, 5 ft. base, 2 1/2 ft. high, W. of the cor.</p>	T11S		R46E	R47E	S36	S31	S 1	S 6	T12S	
T11S											
R46E	R47E										
S36	S31										
S 1	S 6										
T12S											