

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,
T. 12 S., R. 47 E., MOUNT DIABLO MERIDIAN, NEVADA

| | |
|--------|--|
| CHAINS | S. 89°42'50" W., bet. secs. 6 and 31. |
| | Over rolling land. |
| 40.081 | The 1/4 sec. cor. of secs. 6 and 31, monumented with a basalt stone, 15x10x7 ins., firmly set, projecting 7 ins. above the ground, plainly mkd. 1/4 on the N. face, with a mound of stone, 3 ft. base, 1 ft. high, N. of the cor. |
| | At the corner point |
| | Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd. |
| | <p style="text-align: center;">T11S R47E S31 1/4 ——— S 6 T12S 2007</p> |
| | Deposit the original cornerstone alongside the stainless steel post. |
| | From this corner, a rebar, determined to be a reference monument to the original cor., set by Lisle Lowe, Nevada Professional Land Surveyor No. 8423, 1/2 in. diam., firmly set, projecting 6 ins. above the ground, with plastic cap mkd. PLS 8423, as recorded in Nye County, Nevada, Record of Survey, File No. 411077, bears N. 8°50' E., 0.040 chs. dist. |
| | S. 89°41'50" W., beginning new measurement. |
| | Over rolling land. |
| 2.90 | Spur, slopes S. |
| 8.90 | Dry wash, 50 lks. wide, drains SW. |
| 19.90 | Dry wash, 100 lks. wide, drains SE. |
| 39.932 | The cor. of Tps. 11 and 12 S., Rs. 46 and 47 E., hereinbefore described. |
| | <hr/> <p style="text-align: center;">DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 12 S., R. 47 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> |
| | <p style="text-align: center;">Reestablishment of a Portion of the Survey Executed by O.E. Brashears, U.S. Deputy Surveyor, in 1906</p> <hr/> |
| | From the cor. of secs. 5, 6, 7 and 8, described in the field notes of the dependent resurvey of a portion of the subdivisional lines of T. 12 S., R. 47 E., executed under Group No. 772. The cor. is monumented with an iron pipe, (Record, steel pipe), 1 in. diam., no cap, firmly set 6 ins. below the surface of the ground, with a rebar, 5/8 in. diam., |