

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 12 S., R. 47 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	$W \frac{1}{16} \frac{S \ 6}{S \ 7}$
	2007
	Reset the rebar alongside the stainless steel post.

	S. 89°55'00" W., beginning new measurement.
10.00	End of asphalt, beginning of gravel road.
19.60	Center of gravel roads, 30 lks. wide, bears N., E. and S.
19.843	The cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp., hereinbefore described.

	From the cor. of secs. 5, 6, 7 and 8.
	N. 0°14'50"E., bet. secs. 5 and 6.
	Over bare level land.
1.10	Ditch, 3 lks. wide, 2 ft. deep, drains NW.
5.00	Amargosa River, dry, 100 lks. wide, course SW.
14.80	Powerline, bears N. 51° E. and S. 51° W.
15.90	Dry wash, 100 lks. wide, drains SE.
40.174	The 1/4 sec. cor. of secs. 5 and 6, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the subdivisional lines of T. 12 S., R. 47 E., executed under Group No. 772, with a mound of stone, 4 ft. base, 2 ft. high, W. of the cor.

	<p>METES-AND-BOUNDS SURVEY IN SECTION 6, T. 12 S., R. 47 E., MOUNT DIABLO MERIDIAN, NEVADA</p>

	From Angle Point No. 1, sec. 6, identical with the cor. of secs. 5, 6, 7 and 8, hereinbefore described.
	Thence, N. 44°05'20" W., on line 1-2.
2.347	Point for Angle Point No. 2, sec. 6.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap. mkd.