DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY, T. 24 S., R. 60 E., MOUNT DIABLO MERIDIAN, NEVADA

	T. 24 S., R. 60 E., MOUNT DIABLO MERIDIAN, NEVADA
CHAINS	Reestablishment of the Survey Executed by J.M. Brunt and W.H. Proctor, U.S. Deputy Surveyors, in 1881
	Beginning at the point for the cor. of secs. 1, 6, 7 and 12, at proportionate distance; there is no remaining evidence of the original corner.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.
	T24S R60E R61E S 1 S 6 S12 S 7
	2007
	From this point, the cor. of secs. 7, 12, 13 and 18 bears S. 0°20'50" E., 74.648 chs. dist., perpetuated by James L. Marlett, Jr., Nevada Professional Land Surveyor No. 13386, in 2003, monumented with a rebar, 5/8 in. diam., firmly set, projecting 1 in. above the ground, with aluminum cap mkd. PLS 13386, in a mound of stone, 4 ft. base, 2 ft. high, with a basalt stone, 18x12x10 ins., mkd. with 2 grooves and 4 grooves on opposite sides, laying loose in mound, recorded in Clark County, Nevada, as Corner Record No. 20030620-01363.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.
	T24S R60E R61E S12 S 7 S13 S18
	2007
	Insert the rebar, inverted, inside and deposit the mkd. stone alongside the stainless steel post.
,	This control line was fully retraced and careful search was made for evidence of the intervening corner, none of which was recovered.
	N. 0°20'50" W., bet. secs. 1 and 6.
0.60	Wash, 50 lks. wide, drains N. 80° W.
23.80	Ridge, bears NE. and SW.
34.60	Wash, 20 lks. wide, drains NW.
37.324	Point for the $1/4$ sec. cor. of secs. 1 and 6, at proportionate distance; there is no remaining evidence of the original cor.