DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISION-OF-SECTION LINES OF SECTION 5, T. 14 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Reestablishment of a Portion the Subdivision Executed by Robert A. Pratt, Cadastral Surveyor, in 1989
	From the C-N 1/16 sec. cor. of sec. 5, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. as described in the field notes of the subdivision of sec. 5, T. 14 N., R. 27 E., executed under Group No. 670.
	N. 0°08'20" E., on a portion of the N-S center line of sec. 5.
	Over nearly level, gently rolling land covered with low brush, cheat and bunch grass.
9.858	Point for control determined latitudinally at midpoint in distance bet. the C-N 1/16 sec. cor. of sec. 5 and the 1/4 sec. cor. of secs. 5 and 32, on the N. bdy. of the Tp. This point will control the southerly boundary of Indian Trust Patent No. 459 in sec. 5.
	POINT NOT MONUMENTED
9.918	The C-N-N 1/64 sec. cor. of sec. 5, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd. as described in the field notes of the subdivision of sec. 5, T. 14 N., R. 27 E., executed under Group No. 670.
	N. 0°08'20" E., beginning new measurement.
9.798	The 1/4 sec. cor. of secs. 5 and 32, on the N. bdy. of the Tp., hereinbefore described.
	SUBDIVISION OF SECTION 2, T. 14 N., R. 27 E., MOUNT DIABLO MERIDIAN, NEVADA
	From the true point for the 1/4 sec. cor. of secs. 2 and 11.
	N. 0°02'10" E., on the N-S center line of sec. 2.
	Across pond.
1.60	N. bank of pond, bears E. and W.; enter bottom land, through willows, scattered tamarisk, cattails and meadow grass.
5.30	Slough, 90 lks. wide, 3 ft. deep, bears NE. and SW.
9.976	Point for the C-S-S 1/64 sec. cor. of sec. 2.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	C S-S 1/64 S 2 C
	2006