|        | 4  |
|--------|--|
|        | DEPENDENT RESURVEY OF THE FIFTH STANDARD PARALLEL SOUTH,<br>ON THE SOUTH BOUNDARY OF TOWNSHIP 20 SOUTH,<br>THROUGH A PORTION OF RANGE 62 EAST, MOUNT DIABLO MERIDIAN, NEVADA   |
| CHAINS |  |
| 15.059 | The closing cor. of secs. 2 and 3, T. 21 S., R. 62 E., hereinafter described.  |
| 42.610 | The standard 1/4 sec. cor. of sec. 34, monumented with a brass<br>cap, 2 ins. diam., firmly set in concrete, 8 ins. below the<br>surface of the asphalt and in a monument well, mkd. as described<br>in the field notes of the dependent resurvey of T. 21 S.,<br>R. 62 E., executed under Group No. 708.  |
|        | Cor. is located at the intersection of Charleston Boulevard,<br>bears E. and W. and Fog Street, bears N.   |
|        | DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,<br>T. 21 S., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA   |
|        | Reestablishment of a Portion of the Survey Executed by<br>U.S. Deputy Surveyors J.M. Brunt and W.H. Proctor in 1881,<br>a Portion of the Dependent Resurvey Executed by<br>Associate Cadastral Engineer E. Voigt<br>and Assistant Cadastral Engineer J.W. Hardison in 1943,<br>and a Portion of the Dependent Resurvey Executed by<br>Cadastral Surveyor R.A. Pratt in 1991-1994   |
|        | From the 1/4 sec. cor. of secs. 2 and 11, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 21 S., R. 62 E., executed under Group No. 708.   |
|        | N. 89°56'20" W., bet. secs. 2 and 11.  |
|        | Over open, rolling land.   |
| 20.116 | Point for the W 1/16 sec. cor. of secs. 2 and 11, at<br>proportionate distance, based on a private survey conducted by<br>James H. Turner, Nevada Professional Land Surveyor No. 10356, as<br>recorded in Clark County, Nevada, File 87, Page 79 of Surveys,<br>falls in road under construction where it is impracticable to<br>occupy and set a durable article and also not suitable for<br>reference monuments; there is no remaining evidence of the<br>1991-94 corner.   |
| -      | N. 89°57'00" W., beginning new measurement.  |
| 20.114 | The cor. of secs. 2, 3, 10 and 11, determined by Danny L. Rider,<br>Nevada Professional Land Surveyor No. 7169, unrecorded,<br>monumented with a brass cap, 2 ins. diam., firmly set 6 ins.<br>below the surface of the asphalt and in a monument well, mkd.<br>1994 T21S R62E 2 3 10 11 PLS 7169, as shown on map filed<br>March 4, 1997, the survey conducted by James H. Turner,<br>Professional Land Surveyor No. 10356, and recorded in Clark<br>County, Nevada, File 87, Page 79 of Surveys. This is accepted<br>as the best available evidence of the position of the local<br>corner described in the field notes of the dependent resurvey of<br>T. 21 S., R. 62 E., executed under Group No. 708, from which<br>accessories established by person(s) unknown |
|        |  |