

DEPENDENT RESURVEY OF A PORTION OF THE  
IDAHO-NEVADA STATE LINE, FROM MILE POST 104 TO MILE POST 111

CHAINS	
	<p>Retracement of a Portion of the Survey Executed by U.S. Astronomer and Surveyor D.G. Major in 1873, a Portion of the Dependent Resurvey Executed by U.S. Surveyor F.E. Joy in 1911 and a Portion of the Dependent Resurvey Executed by Cadastral Surveyor W.D. Kimmel in 2004-05</p> <hr/> <p>Beginning at the 104 Mile Post, monumented with a basalt stone, 28x20x5 ins., firmly set in a mound of stone, 6 ft. base, 3 ft. high, mkd. I 42 L on the N. face and N 104 on the S. face.</p> <p>N. 89°28'40" W., on the 105th mile.</p>
35.408	Point for the closing cor. of Tps. 47 N., Rs. 52 and 53 E., hereinafter described.
65.868	From this point, the closing cor. of secs. 26 and 27, T. 16 S., R. 3 E., Boise Meridian, Idaho, bears SOUTH, 0.131 chs. dist., monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above a mound of stone, 3 ft. diam., 1 ft. high, with brass cap mkd. T16S R3E S26 S27 CC 1912. Cor. is located below the top of bluff, at base of small cliff, 30 ft. high, on west slope of steep rocky mountain.
80.738	True point for the 105 Mile Post, at proportionate distance; falls in unstable rock slide area, where it is impractical to establish a permanent monument.
	<hr/> <p>N. 89°28'40" W., on the 106th mile.</p>
20.184	The witness cor. to the 105 Mile Post, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above the ground, in a mound of stone, 3 ft. base, to top, with aluminum cap mkd. as described in the field notes of the dependent resurvey of a portion of the Idaho-Nevada State Boundary, executed under Group No. 1184, Idaho.
	<hr/> <p>N. 89°55'00" W., beginning new measurement.</p>
14.267	Point for the closing cor. of secs. 1 and 2, hereinafter described.
34.406	Point for the E 1/16 sec. cor., on the N. bdy. of sec. 2, hereinafter described.
44.928	The closing cor. of secs. 27 and 28, on the S. bdy. of T. 16 S., R. 3 E., Boise Meridian, Idaho, monumented with a rebar, 3/4 in. diam., firmly set in drill hole in boulder, projecting 10 ins. above the ground and in a mound of stone, 4 ft. base, to top, with aluminum cap mkd. as described in the field notes of the dependent resurvey of a portion of the subdivisional lines, T. 16 S., R. 3 E., executed under Group No. 1184, Idaho.