

DEPENDENT RESURVEY OF A PORTION OF THE
IDAHO-NEVADA STATE LINE, FROM MILE POST 104 TO MILE POST 111

CHAINS	
65.558	<p>From this point, the closing cor. of secs. 26 and 27, T. 16 S., R. 2 E., Boise Meridian, bears SOUTH, 0.006 chs. dist., monumented with an iron post, 1 in. diam., firmly set, projecting 2 ft. above the ground, at the cor. of fences extending E, W. and N., with brass cap mkd. CC T16S R2E IDA S26 S27 1912, with a mound of stone, 5 ft. diam., 3 ft. high, E. of corner.</p>
71.372	<p>From this point, the 1/4 sec. cor. for sec. 1 only, on the N. bdy. of sec. 1, T. 47 N., R. 51 E., Mount Diablo Meridian, bears SOUTH, 0.073 chs. dist., monumented with a bent iron post, 1 in. diam., projecting 15 ins. above the ground, leaning southerly, with brass cap mkd. 1/4 CC S1 10 NEV 191. Cor. is located 10 lks. E. of the cor. of fences extending E., W. and S.</p>
80.702	<p>The 111 Mile Post, monumented with an iron post, 3 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the Idaho-Nevada State Boundary, executed under Instructions dated April 27, 1911.</p>
<hr/> <p>DEPENDENT RESURVEY OF THE SOUTH BOUNDARY, T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/>	
<p>Reestablishment of the Survey Executed by U.S. Surveyor F.E. Joy in 1911</p> <hr/>	
<p>From the cor. of Tps. 46 and 47 N., Rs. 52 and 53 E., monumented with an iron post, 3 ins. diam., set flush with the surface of the ground, with brass cap mkd. as described in the field notes of the survey of the east boundary of T. 46 N., R. 52 E., executed under Instructions dated April 27, 1911.</p>	
<p>S. 89°56'30" W., bet. secs. 1 and 36.</p>	
26.00	<p>Owyhee River, 2 chs. wide, course NW.</p>
39.650	<p>The 1/4 sec. cor. of secs. 1 and 36, monumented with a rusted iron post, 1 in. diam., 36 ins. long, bent at base, loosely set in a mound of stone, with brass cap mkd. as described in the field notes of the survey of the north boundary of T. 46 N., R. 52 E., executed under Instructions dated April 27, 1911.</p>
<p>At the corner point</p>	
<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, in a collar of stone, with brass cap mkd.</p>	