## METES-AND-BOUNDS SURVEY OF LOT 3 IN SECTION 26, T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

	T. 47 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA
CHAINS	The boundary of Lot No. 3 was based on the supplemental plat dated February 8, 1957 and the patent issued May 15, 1957.
	Beginning at the point for Angle Point No. 1, Lot 3, determined at record angle and distance from Angle Point No. 4, Lot 3.

Set a copper coated steel stake, 20 ins. long, 9/16 in. diam. flush with the surface of the ground, with brass cap,  $1\ 1/2$  ins. diam., mkd.

T47N R52E

AP1 S26 LOT 3

2006

Thence N.  $89^{\circ}59'40"$  W., on line 1-2, Lot 3.

4.495 Intersect the N. and S. center line of the SE1/4 of sec. 26, from which the SE 1/16 sec. cor. of sec. 26 bears S. 0°11'20" E., 4.047 chs. dist., hereinbefore described.

Point for Angle Point No. 2, Lot 3, determined at record angle and distance from Angle Point No. 3, Lot 3.

Set a copper coated steel stake, 20 ins. long, 9/16 in. diam., flush with the surface of the ground, with brass cap,  $1\ 1/2$  ins. diam., mkd.

Thence S.  $0^{\circ}04'10"$  E., on line 2-3, Lot 3.

4.045 Point for Angle Point No. 3, Lot 3, determined at record distance from the SE 1/16 sec. cor. of sec. 26, and on the E-W center line of the SE1/4 of sec. 26, identical with line 3-4 of Lot 3.

Set a copper coated steel stake, 20 ins. long, 9/16 in. diam., flush with the surface of the ground, with brass cap,  $1\ 1/2$  ins. diam., mkd.