

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,
T. 10 S., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Reestablishment of the Survey Executed by U.S. Deputy Surveyors W.F. Benson and C.F. Putnam in 1881																
	<p>Beginning at the cor. of secs. 25, 30, 31 and 36, perpetuated by R.L. Carpenter, Nevada Professional Land Surveyor No. 2708, not recorded, monumented with a rebar, 5/8 in. diam., firmly set in a mound of stone, 4 ft. base, 3 ft. high, with aluminum cap mkd. LAPS L67 RLS 2708, alongside of which is a basalt stone 16x12x10 ins., loosely set, mkd. with 1 groove on S. and 5 grooves on N. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <table border="1" data-bbox="883 751 1029 869"> <tr><td colspan="2" style="text-align:center">T10S</td></tr> <tr><td style="text-align:center">R62E</td><td style="text-align:center">R63E</td></tr> <tr><td style="text-align:center">S25</td><td style="text-align:center">S30</td></tr> <tr><td style="text-align:center">S36</td><td style="text-align:center">S31</td></tr> </table> <p style="text-align:center">2005</p> <p>A careful search was made for evidence of the position determined as the cor. of secs. 25, 30, 31 and 36, by Richard J. Baughman, Nevada Professional Land Surveyor No. 2162, as recorded in Lincoln County, Nevada, Plat Book No. A, Page 83, Inst. No. 50129. No monument was found.</p> <p>Deposit the rebar and the original stone alongside the stainless steel post.</p> <p>N. 1°52'10" E., bet. secs. 25 and 30.</p> <p>Over rolling land covered with creosote, chaparral and scattered cacti.</p> <p>17.50 Enter wash, drains SW.</p> <p>22.00 Leave wash, ascend.</p> <p>38.00 Ridge, bears NE. and SW.</p> <p>40.522 The 1/4 sec. cor. of secs. 25 and 30, monumented with a limestone, 15x8x7 ins., loosely set in a mound of stone, 3 ft. base, 1 1/2 ft. high, dimly mkd. 1/4 on W. face.</p> <p>At the corner point</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2-in. stem, flush in rock, with top mkd.</p> <table border="1" data-bbox="883 1717 1029 1822"> <tr><td colspan="2" style="text-align:center">T10S</td></tr> <tr><td colspan="2" style="text-align:center">1/4</td></tr> <tr><td style="text-align:center">R62E</td><td style="text-align:center">R63E</td></tr> <tr><td style="text-align:center">S25</td><td style="text-align:center">S30</td></tr> </table> <p style="text-align:center">2005</p>	T10S		R62E	R63E	S25	S30	S36	S31	T10S		1/4		R62E	R63E	S25	S30
T10S																	
R62E	R63E																
S25	S30																
S36	S31																
T10S																	
1/4																	
R62E	R63E																
S25	S30																