## DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY, T. 10 S., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA

	1. 10 S., K. 02 E., MOUNT DIADED MERIDIAN, NEVADA
CHAINS 83.60	Spur, slopes W.
87.618	The cor. of secs. 7, 12, 13 and 18, perpetuated by R.L. Carpenter, Nevada Professional Land Surveyor No. 2708, not recorded, monumented with a rebar, 3/4 in. diam., firmly set flush with the ground, with aluminum cap mkd. LAPS RLS 2708, alongside of which is a limestone, 15x12x10 ins., loosely set, mkd. with 2 grooves on N. face only.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.
	T10S R62E R63E S12 S 7 S13 S18
	2005
	Deposit the rebar and the original stone alongside the stainless steel post.
	DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 10 S., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA
	Reestablishment of the Survey Executed by U.S. Deputy Surveyors W.F. Benson and C.F. Putnam in 1881
	From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp., hereinbefore described.
	N. 89°11'20" W., bet. secs. 25 and 36.
	Over rolling land covered with creosote, chaparral and scattered cacti.
10.00	Spur, slopes SW.
16.20	Old highway, 40 lks. wide, bears S. 10 1/2° E., and N. 10 1/2° W., over nearly level land.
19.278	Point for the E 1/16 sec. cor. of secs. 25 and 36.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.
	E $1/16 \frac{S25}{S36}$
	2006