

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,
T. 11 S., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Reestablishment of the Survey Executed by U.S. Deputy Surveyors W.F. Benson and C.F. Putnam in 1881</p>
	<p>Beginning at the cor. of secs. 13, 18, 19 and 24, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground and in a collar of stone, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the W. bdy. of T. 11 S., R. 63 E., executed under Group No. 824.</p> <p>N. 0°19'10" W., bet. secs. 13 and 18.</p> <p>Over flats covered with creosote, chaparral and scattered cacti.</p>
0.02	Cor. of fences extending S. and W.
19.20	U.S. Highway No. 93, 40 lks. wide, bears S. 5 1/4° E. and N. 5 1/4° W.
40.025	<p>The 1/4 sec. cor. of secs. 13 and 18, monumented with a granite stone, 13x13x6 ins., firmly set 6 ins. in the ground, mkd. 1/4 on E. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T11S 1/4 R62E R63E S13 S18</p> <p>2005</p> </div> <p>Deposit the original stone alongside the stainless steel post.</p>
	<p>N. 0°06'50" W., beginning new measurement.</p>
6.10	Underground fiber optic cable, bears S. 5 1/4° E. and N. 5 1/4° W.
40.136	<p>The cor. of secs. 7, 12, 13 and 18, perpetuated by Jay M. Rassler, Nevada Professional Land Surveyor No. 1624, not recorded, monumented with a rebar, 1 in. diam., with brass tag mkd. RLS 1624, firmly set in mound of stone, 3 ft. base, 1 ft. high, alongside of which is a granite stone, 15x11x11 ins., loosely set, mkd. with 4 grooves on S. and 2 grooves on N. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p>