

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 11 S., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T11S R62E S12 1/4 <u> </u> S13</p> <p style="text-align: center;">2005</p> <p>Deposit the original stone alongside the stainless steel post.</p> <hr style="width: 20%; margin: auto;"/> <p>S. 89°18'00" W., beginning new measurement.</p>
19.930	<p>Point for the W 1/16 sec. cor. of secs. 12 and 13.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">W 1/16 <u> </u> S12 S13</p> <p style="text-align: center;">2006</p>
31.90	<p>Dry wash, 50 lks. wide, drains SE.</p>
39.860	<p>The cor. of secs. 11, 12, 13 and 14.</p>
<hr/> <p>SUBDIVISION OF SECTION 13, T. 11 S., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/>	
	<p>From the 1/4 sec. cor. of secs. 13 and 24.</p> <p>N. 0°11'50" W., on the N-S center line of sec. 13.</p>
35.50	<p>Gravel road, 30 lks. wide, SE. and NW.</p>
40.014	<p>Point for the center 1/4 sec. cor. of sec. 13, at intersection with the E-W center line.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T11S R62E C 1/4 S13</p> <p style="text-align: center;">2006</p>
60.148	<p>Point for the C-N 1/16 sec. cor. of sec. 13.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p>