

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,
T. 23 S., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>Reestablishment of the Survey Executed by T.A. Magee in 1883 and the Resurvey Executed by C.S. Swanholm, Andrew Nelson and R.C. Yundt in 1931</p>
	<p>Beginning at the cor. of secs. 13, 18, 19 and 24, monumented with an iron post, 2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of the 1931 dependent resurvey executed under Group No. 169.</p>
	<p>N. 0°13'30" E., bet. secs. 13 and 18.</p>
	<p>Over nearly level land.</p>
7.40	<p>Dirt road, 18 lks. wide, bears N. 40° E. and S. 40° W.</p>
9.50	<p>Powerline, bears N. 37° E. and S. 37° W.</p>
20.162	<p>Point for the S 1/16 sec. cor. of secs. 13 and 18.</p>
	<p>POINT NOT MONUMENTED</p>
24.50	<p>Dirt road, 18 lks. wide, parallels powerline.</p>
26.411	<p>Intersect power transmission line and centerline of right-of-way N-10683, bears N. 43°20'30" E. and S. 43°20'30" W., and monument established by Robert L. Carpenter, Nevada Professional Land Surveyor No. 2708, a rebar, 5/8 in. diam., firmly set flush with the surface of the ground, with aluminum cap mkd. LAPS C927 RLS2708, later recovered and utilized by Donald R. Mertens, Nevada Professional Land Surveyor No. 8879, as recorded in Clark County, Nevada, File 61, Page 68 of Surveys.</p>
	<p>From this point, the center of power transmission tower No. 310-3, and monument for the centerline of right-of-way N-10683 established by Robert L. Carpenter, Nevada Professional Land Surveyor No. 2708, a rebar, 5/8 in. diam., firmly set flush with the surface of the ground, with aluminum cap mkd. LAPS L42R T327 RLS2708, later recovered and utilized by Donald R. Mertens, Nevada Professional Land Surveyor No. 8879, as recorded in Clark County, Nevada, File 61, Page 68 of Surveys, bears N. 43°20'30" E., 4.782 chs. dist.</p>
	<p>From this same point, the center of power transmission tower No. 310-4, and monument for the centerline of right-of-way N-10683 established by Robert L. Carpenter, Nevada Professional Land Surveyor No. 2708, a rebar, 5/8 in. diam., firmly set flush with surface of the ground, with aluminum cap mkd. LAPS L42R T3276 RLS2708, later recovered and utilized by Donald R. Mertens, Nevada Professional Land Surveyor No. 8879, as recorded in Clark County, Nevada, File 61, Page 68 of Surveys, bears S. 43°20'30" W., 14.834 chs. dist.</p>
28.628	<p>Point for a witness point and intersection with the northwesterly line of right-of-way N-10683, 100 feet northwesterly and parallel with the centerline, monumented by Robert L. Carpenter, Nevada Professional Land Surveyor No. 2708, with a rebar, 5/8 in. diam., firmly set flush with the surface of the ground, with aluminum cap mkd. LADWP SURVEY POINT NO L42R R627 RLS 2708 POWER SYSTEM, later recovered and utilized by</p>