

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,
T. 23 S., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

- 3.60 Rocky spur, slopes E., descend precipitous and broken E. slope over large slides and outcrops.
- 20.133 Point for the S 1/16 sec. cor. of secs. 7 and 12.
POINT NOT MONUMENTED
- 30.40 Draw, drains E.; ascend abrupt broken SE. slope.
- 40.266 The 1/4 sec. cor. of secs. 7 and 12, monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd. as described in the field notes of the 1931 dependent resurvey executed under Group No. 169. Add the marks T23S R62E R63E 2008 on the brass cap.

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,
T. 23 S., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of the Survey Executed by T.A. Magee in 1883 and
the Resurvey Executed by C.S. Swanholm in 1931

From the cor. of secs. 5, 6, 31 and 32, reestablished by J.P. Higgins, Nevada Professional Land Surveyor No. 13601, monumented with a rebar, 5/8 in. diam., firmly set, projecting 3 ins. above the ground, with aluminum cap mkd. J.P. Higgins WOOD RODGERS PLS 13601, as recorded in Clark County, Nevada, File 119, Page 4 of Plats, utilizing the reestablishment by Sam Long, Nevada Professional Land Surveyor No. 9047, as recorded in Clark County, Nevada, File 112, Page 77 of Surveys. This is accepted as a careful and faithful reestablishment of the position of the original corner.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with a brass cap mkd.

T22S R63E	
S31	S32
S 6	S 5
T23S	

2007

Insert the rebar inside the stainless steel post.

Cor. falls at the NE. cor. of a masonry fence which surrounds water storage tanks. Fence bears E. and W.

From this corner, the 1/4 sec. cor. of secs. 5 and 32, monumented with an iron post, 1 in. diam., firmly set in a mound of stone, with brass cap mkd. as described in the field notes of the 1931 dependent resurvey of the S. bdy. of T. 22 S., R. 63 E., executed under Group No. 169, bears N. 89°45'00" E., 39.994 chs. dist. Add the marks T22S T23S R63E 2008 on the brass cap.