

DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 3331,
T. 1 N., R. 38 1/2 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS																					
2.970	<p>Point for Cor. No. 6, Mineral Survey No. 3331, Alum Pure Placer, determined by Grant Boundary proportion; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td></td><td>3331</td><td></td></tr> <tr><td></td><td>SPP</td><td></td></tr> <tr><td></td><td colspan="2"><hr/></td></tr> <tr><td></td><td>6</td><td>T1N</td></tr> <tr><td>APP</td><td></td><td>R38 1/2E</td></tr> <tr><td>3331</td><td></td><td>S29</td></tr> </table> <p>2008</p> </div>		3331			SPP			<hr/>			6	T1N	APP		R38 1/2E	3331		S29		
	3331																				
	SPP																				
	<hr/>																				
	6	T1N																			
APP		R38 1/2E																			
3331		S29																			
	<hr/> <p>S. 1°12'40" E., on line 6-1, Mineral Survey No. 3331, Alum Pure Placer.</p>																				
10.011	<p>Cor. No. 1, Mineral Survey No. 3331, Alum Pure Placer.</p>																				
	<hr/> <div style="text-align: center;"> <p>SURVEY OF THE NORTH BOUNDARY, T. 1 N., R. 38 1/2 E., MOUNT DIABLO MERIDIAN, NEVADA</p> </div> <hr/>																				
	<p>From the cor. of Tps. 1 and 2 N., Rs. 38 and 38 1/2 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of the survey of T. 1 N., R. 38 E., executed concurrently under this same group.</p> <p>N. 89°58'00" E., bet. secs. 6 and 31.</p> <p>Over nearly level land.</p>																				
26.40	<p>Dry wash, 30 lks. wide, drains N.</p>																				
40.000	<p>Point for the 1/4 sec. cor. of secs. 6 and 31.</p>																				
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td></td><td>T2N</td><td>R38</td><td>1/2E</td></tr> <tr><td></td><td></td><td>S31</td><td></td></tr> <tr><td></td><td>1/4</td><td colspan="2"><hr/></td></tr> <tr><td></td><td></td><td>S 6</td><td></td></tr> <tr><td></td><td></td><td>T1N</td><td></td></tr> </table> <p>2008</p> </div>		T2N	R38	1/2E			S31			1/4	<hr/>				S 6				T1N	
	T2N	R38	1/2E																		
		S31																			
	1/4	<hr/>																			
		S 6																			
		T1N																			
75.80	<p>Dry wash, 40 lks. wide, drains N.</p>																				
80.000	<p>Point for the cor. of secs. 5, 6, 31 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>																				