

DEPENDENT RESURVEY OF THE MOUNT DIABLO BASE LINE,
THROUGH A PORTION OF RANGE 39 EAST,
MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>Reestablishment of the Survey Executed by G.H. Perrin, U.S. Deputy Surveyor, in 1884, and the Dependent Resurvey Executed by J.A. Bastian and S.R. Lambeth, Cadastral Surveyors, in 1982</p> <hr/>
	<p>The original standard corner monuments found on this line will now function as angle points.</p>
	<p>Beginning at the standard cor. of secs. 33 and 34, T. 1 N., R. 39 E., established by Bastian and Lambeth in 1982, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above the ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of the Mount Diablo Base Line, through a portion of R. 39 E., executed under Group No. 600, and a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p>
	<p>N. 89°54'00" W., on the S. bdy. of sec. 33.</p>
	<p>Over low rolling hills.</p>
5.358	<p>The closing cor. of Tps. 1 S., Rs. 39 and 40 E., monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of the E. bdy. of T. 1 S., R. 39 E., executed under Group No. 600, and a mound of stone, 3 ft. base, 2 ft. high, S. of cor.</p>
7.208	<p>An angle point on the S. bdy. of sec. 33, identical with Nevada Planning Division (N.P.D.) triangulation station "BASE", monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of the Mount Diablo Base Line, through a portion of R. 39 E., executed under Group No. 600, and a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p> <hr/>
	<p>N. 89°37'30" W., beginning new measurement, on the Mount Diablo Base Line.</p>
	<p>Over low rolling hills.</p>
32.00	<p>Spur, slopes SW.</p>
32.793	<p>Point for the new standard 1/4 sec. cor. of sec. 33, T. 1 N., R. 39 E., established 40 chs. W. in departure from the standard cor. of secs. 33 and 34, T. 1 N., R. 39 E.</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p style="text-align: center;">SC T1N R39E <u>1/4 S33</u></p>
	<p style="text-align: center;">2008</p>