

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,
T. 19 N., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
22.615	Point for a witness point, at intersection of the westerly right-of-way line of the Nevada Northern Railway with the line bet. secs. 1 and 36, hereinafter described.
39.790	The cor. of secs. 1, 2, 35 and 36, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the N. bdy. of T. 19 N., R. 63 E., executed under Group No. 413.
DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 19 N., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA Reestablishment of a Portion of the Survey Executed by U.S. Deputy Surveyors E.B. Monroe and A.G. Bateman in 1872	
	From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the S. bdy. of T. 19 N., R. 63 E., executed under Group No. 413, with a mound of stone, 2 ft. base, 1/2 ft. high, W. of cor. N. 0°02'20" E., bet. secs. 35 and 36. Over gently rolling land.
39.936	Point for the 1/4 sec. cor. of secs. 35 and 36, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd. T19N R63E 1/4 S35 S36 2006 Set a steel fence post alongside the stainless steel post.
50.10	Bladed dirt road, bears NNE. and SSW.
79.872	The cor. of secs. 25, 26, 35 and 36, reestablished by Dean Neubauer, Nevada Professional Land Surveyor No. 9392, monumented with a rebar, 18 ins. long, 5/8 in. diam., firmly set, projecting 3 ins. above the ground, with aluminum cap, 3 ins. diam., mkd. SUMMIT ENG CORP T19N R63E 25 26 35 36 PLS 9392 2003, recorded in White Pine County, Nevada, as Map No. 806, File No. 318935, and is accepted as a careful and faithful reestablishment of the position of the original corner. At the corner point Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.