

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,
T. 18 N., R. 63 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	<p>Reestablishment of a Portion of the Survey Executed by U.S. Deputy Surveyors E.B. Monroe and A.G. Bateman in 1872, and a Portion of the Dependent Resurvey Executed by Cadastral Surveyors H.G. Parker and J.D. Sorensen in 1963</p> <hr/>
	<p>Beginning at the point for the cor. of secs. 7, 12, 13 and 18, on the E. bdy. of the Tp., at proportionate distance; there is no remaining evidence of the original corner. Point falls in collection ditch, west of the main tracks of the Nevada Northern Railway, where it is impractical to establish a permanent monument. The witness cor. of secs. 7, 12, 13 and 18 is hereinafter described.</p>
	<p>From this point, the cor. of secs. 19, 24, 25 and 30 bears S. 0°05'20" E., 159.840 chs. dist., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 10 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the E. bdy. of T. 19 N., R. 63 E., executed under Group No. 413.</p>
	<p>Cor. is located at the cor. of fences extending S. and E.</p>
	<p>The control line was fully retraced and a careful search was made for intervening corners, none of which were found.</p>
	<p>N. 0°05'20" W., bet. secs. 7 and 12.</p>
	<p>Over gently rolling land.</p>
4.50	<p>Center of the Nevada Northern Railway tracks, bears N. 9° W. and S. 9° E.; enter meadow.</p>
39.960	<p>Point for the 1/4 sec. cor. of secs. 7 and 12, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>
	<p>T18N 1/4 R63E R64E S12 S 7 2006</p>
51.90	<p>Bladed dirt road, bears NW. and SE.; enter rolling land.</p>
79.920	<p>The cor. of secs. 1, 6, 7 and 12, monumented with an unrecorded rebar, 12 ins. long, 5/8 in. diam., firmly set 2 ins. below the surface of the ground, with aluminum cap, 1 1/2 ins. diam., mkd. FONGER RLS, with the remains of a wood post, 18 ins. long, 2 ins. diam., squared on one side, wired to a steel fence post, set alongside the rebar. This position is accepted as a careful and faithful perpetuation of the position of the original corner.</p>
	<p>At the corner point</p>
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>