

DEPENDENT RESURVEY OF THE SECOND STANDARD PARALLEL SOUTH,
THROUGH A PORTION OF RANGE 61 EAST,
MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
12.193	Point for the closing cor. of Tps. 9 S., Rs. 61 and 62 E., hereinafter described, fence bears easterly and northwesterly.
40.292	The standard 1/4 sec. cor. of sec. 36, monumented with a limestone, 15x12x5 ins., firmly set 4 ins. in the ground, in a mound of stone, 4 ft. base, 1 ft. high, plainly mkd. 1/4 on N. face.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground to bedrock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.
	<div style="text-align: center;"> SC T8S R61E 1/4 S36 </div>
	2009
	Bury the mkd. stone alongside the stainless steel post.
	<hr/> <p style="text-align: center;">DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY, T. 9 S., R. 61 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/>
	<p style="text-align: center;">Reestablishment of the Survey Executed by U.S. Transitman H.G. Mason in 1917</p> <hr/>
	From the 1/4 sec. cor. for sec. 1, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above the ground, with brass cap mkd. as described in the field notes of T. 9 S., R. 62 E., executed under Group No. 49, with a mound of stone, 4 ft. base, 2 ft. high, W. of cor.
	N. 0°03'20" W., on the E. bdy. of sec. 1, T. 9 S., R. 61 E.
	Over rolling land, covered with greasewood and sagebrush.
4.316	The 1/4 sec. cor. for sec. 6 only, T. 9 S., R. 62 E., hereinafter described.
44.562	Intersect the Second Standard Parallel South.
	Point for the closing cor. of Tps. 9 S., Rs. 61 and 62 E.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.