

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 9 S., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA

## CHAINS

The closing cor. of secs. 4 and 5, monumented with an iron post, 2 ins. diam., firmly set, projecting 8 ins. above the ground, with brass mkd. as described in the field notes of T. 9 S., R. 62 E., executed under Group No. 49.

From this cor., the standard cor. of secs. 32 and 33, T. 8 S., R. 62 E., bears N. 89°42'20" E., 8.604 chs. dist., hereinbefore described.

The point for the N. 1/4 sec. cor. of sec. 4 is on the Second Standard Parallel South and at midpoint in departure on the N. bdy. of sec. 4.

Set a copper-coated steel stake, 24 ins. long, 1/2 in. diam., 12 ins. below the surface of gravel road, with top mkd.

T8S R62E

1/4 S 4

T9S

2009

from which

A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over plastic-encased magnet, for a reference monument, bears S. 62°59' E., 0.436 chs. dist., with brass cap mkd. RM 1/4 S4 28.8 FT TO COR 2009 and an arrow pointing to the cor.

A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over plastic-encased magnet, for a reference monument, bears S. 14°22' W., 0.479 chs. dist., with brass cap mkd. RM 1/4 S4 31.6 FT TO COR 2009 and an arrow pointing to the cor.

Cor. is located in center of bladed gravel road, 40 lks. wide, bears NE. and SW.

From this point, the standard 1/4 sec. cor. of sec. 33, T. 8 S., R. 62 E., bears S. 89°53'30" E., 10.593 chs. dist., hereinbefore described.

The point for the W 1/16 sec. cor. of sec. 4 is on the Second Standard Parallel South and at midpoint in departure bet. the closing cor. of secs. 4 and 5 and the N. 1/4 sec. cor. of sec. 4.

POINT NOT MONUMENTED

From this point, the standard cor. of secs. 32 and 33, T. 8 S., R. 62 E., bears N. 89°53'30" W., 11.302 chs. dist., hereinbefore described.