

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 9 S., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA

|        |  |
|--------|--|
| CHAINS | N. 0°05'10" W., beginning new measurement.   |
| 19.999 | <p>The N 1/16 sec. cor. of secs. 5 and 6, determined by the U.S. Fish and Wildlife Service, unrecorded, monumented with a concrete post, 3 ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd. N 1/16 S5 S6 1963, and is accepted as a careful and faithful determination of the position of the corner.</p> <p>Cor. is located in a barbed wire fence, bears SE. and NW.</p> <hr/> <p>N. 0°03'10" W., beginning new measurement.</p>  |
| 20.596 | <p>Intersect the Second Standard Parallel South.</p> <p>Point for the closing cor. of secs. 5 and 6.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T8S R62E<br/>S31</p> <hr/> <p>S 6   S 5<br/>T9S<br/>CC</p> <p>2009</p> </div> <p>From this point, the original closing cor. of secs. 5 and 6, monumented with an iron post, 2 ins. diam., firmly set, projecting 12 ins. above the ground, with brass mkd. as described in the field notes of T. 9 S., R. 62 E., executed under Group No. 49, bears N. 0°03'10" W., 0.021 chs. dist. Add the marks AM to the brass cap, invert the iron post and bury in place.</p> <p>From this same point, the standard cor. of secs. 31 and 32, T. 8 S., R. 62 E., bears N. 89°41'50" E., 8.516 chs. dist., hereinbefore described.</p> <hr/> <p>The point for the N. 1/4 sec. cor. of sec. 5 is on the Second Standard Parallel South and at midpoint in departure on the N. bdy. of sec. 5.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T8S R62E</p> <hr/> <p>1/4 S 5<br/>T9S</p> <p>2009</p> </div> |