DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 9 S., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA

	1. 9 3., R. 02 E., MOONI DIADLO MERIDIAN, NEVADA
CHAINS	From this point, the standard 1/4 sec. cor. of sec. 32, T. 8 S., R. 62 E., bears N. 89°41'40" E., 8.529 chs. dist., hereinbefore described.
	The point for the N. 1/4 sec. cor. of sec. 6 is on the Second Standard Parallel South and at proportionate distance in departure bet. the local E 1/16 sec. cor. of sec. 6, on the N. bdy. of sec. 6, and the closing cor. of Tps. 9 S., Rs. 61 and 62 E.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T8S R62E
	1/4 S 6 T9S
	2009
	Cor. is located 1 1/2 lks. N. of a barbed wire fence, bears E. and W.
	From this point, the standard 1/4 sec. cor. of sec. 31, T. 8 S., R. 62 E., bears N. 89°39'50" E., 8.390 chs. dist., hereinbefore described.
	SUBDIVISION OF SECTION 4, T. 9 S., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA
	From the 1/4 sec. cor. of secs. 4 and 9.
	N. 0°07'50" E., on the N-S center line of sec. 4.
	Over gently rolling land, covered with greasewood and sagebrush.
20.140	Point for the C-S 1/16 sec. cor. of sec. 4.
	POINT NOT MONUMENTED
40.280	The center 1/4 sec. cor. of sec. 4, determined by the U.S. Fish and Wildlife Service, unrecorded, monumented with an iron pipe, 3 ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap concreted into top of pipe, mkd. C 1/4 S4 1963, and is accepted as a careful and faithful determination of the position of the corner.
	N. 0°02'00" E., beginning new measurement.
7.50	Barbed wire fence, bears SE. and NW.
7.70	Underground fiber optic line, bears SE. and NW.
8.70	U.S. Highway No. 93, asphalt surfaced, 40 lks. wide, bears SE. and NW.