TOWNSHIP 18 SOUTH, RANGE 60 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

The 1974 mean magnetic declination is 15° E., as shown on U.S.G.S. 7 1/2 minute quadrangle map "CORN CREEK SPRINGS, NEV.", dated 1974.

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY, T. 18 S., R. 60 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of the Survey Executed By U.S. Deputy Surveyors R.H. Woods and W.H. Myrick in 1882

Beginning at the cor. of Tps. 18 and 19 S., Rs. 60 and 61 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above the ground, with brass cap mkd. as described in the field notes of T. 19 S., R. 61 E., executed under Group No. 683, from which the remaining 1990 accessory

A cross (X) etched on a steel plate, 4 ins. square, mkd. PWF414 77299 112 57914, firmly attached to a powerline pole, bears S. 43°20' W., 1.476 chs. dist.

N. $0^{\circ}59'50''$ E., bet. secs. 31 and 36.

Ascend gradual SW slope, with scattered yucca and greasewood.

40.696

The 1/4 sec. cor. of secs. 31 and 36, perpetuated by person(s) unknown, monumented with a rebar, 5/8 in. diam., 12 ins. long, firmly set, projecting 4 ins. above the ground, with a limestone, 18x11x6 ins., lying alongside, mkd. 1/4 on one face.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.

T18S R60E R61E 1/4 S36 S31

2009

Insert the rebar inside the stainless steel post and bury the mkd. stone alongside.

Cor. is located E., 30 lks. of a concrete flood canal, bears N. and S.

N. 0°03'30" E., beginning new measurement.

40.553

The cor. of secs. 25, 30, 31 and 36, perpetuated by Robert L. Pounds, Nevada Professional Land Surveyor No. 13867, monumented with a rebar, 5/8 in. diam., 12 ins. long, firmly set, projecting 6 ins. above the ground, in a mound of stone,