TOWNSHIP 20 SOUTH, RANGE 54 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS The corner of secs. 26, 27, 34 and 35 is as follows: Latitude: 36°10'33.628" N. Longitude: 115°53'13.006" W. The June 21, 2010 mean magnetic declination was determined to be 12°37' E., as obtained from the National Oceanic and Atmospheric Administration's declination calculator. DEPENDENT RESURVEY OF THE FIFTH STANDARD PARALLEL SOUTH, THROUGH A PORTION OF RANGE 54 EAST, MOUNT DIABLO MERIDIAN, NEVADA Reestablishment of the Survey Executed by U.S. Deputy Surveyor T. Binge in 1881 Beginning at the standard cor. of secs. 34 and 35, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, flush in a collar of stone, with brass cap mkd. as described in the field notes of the 2001-06 dependent resurvey of the Fifth Standard Parallel South, through a portion of Range 54 East, executed under Group No. 799. N.  $89^{\circ}59'20''$  W., on the S. bdy. of sec. 34. Gradual descent, through creosote and scattered cacti. 33.95 Toe of dirt and rock berm, 10 ft. high, bears S. 78° E. and N. 78° W. Continue over dirt and rock berm. Toe of dirt and rock berm, 10 ft. high, bears N. 40° E. and S. 40° W. 38.10 Continue gradual descent, through creosote and scattered cacti. 38.457 The 1/4 sec. cor. of sec. 3, T. 21 S., R. 54 E., established by person(s) unknown, perpetuated by Kay L. Adams, Nevada Professional Land Surveyor No. 2050, in 1973, monumented with a rebar, 5/8 in. diam., firmly set, 2 ins. below the ground, with aluminum cap mkd. VTN ENGR CO RLS 2050, with a limestone, 12x8x8 ins., mkd. 1/4 on one side, laying loose alongside, as recorded in Clark County, Nevada, File 26, Page 29 of Surveys, filed as Instrument No. 301280. 40.900 The standard 1/4 sec. cor. of sec. 34, reestablished by Kay L. Adams, Nevada Professional Land Surveyor No. 2050, in 1973, monumented with a rebar, 5/8 in. diam., firmly set flush with the ground, with aluminum cap mkd. VTN ENGR CO RLS 2050, as recorded in Clark County, Nevada, File 26, Page 29 of Surveys, filed as Instrument No. 301280, and is accepted as a careful and faithful reestablishment of the position of the original corner. At the corner point Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.