

DEPENDENT RESURVEY OF THE FIFTH STANDARD PARALLEL SOUTH,
THROUGH A PORTION OF RANGE 54 EAST,
MOUNT DIABLO MERIDIAN, NEVADA

<p>CHAINS</p> <p>20.441</p> <p>7.35</p> <p>42.152</p>	<p>The standard cor. of secs. 33 and 34, perpetuated by Kay L. Adams, Nevada Professional Land Surveyor No. 2050, in 1973, monumented with a rebar, 5/8 in. diam., firmly set 2 ins. below the ground, with aluminum cap mkd. VTN ENGR CO RLS 2050, as shown on Sheet No. 3 of 3 Sheets, Calvada Valley Unit No. 9A, recorded in Nye County, Nevada, filed as Instrument No. 36870. This corner was accepted as a careful and faithful remonumentation of the position of the original corner in the 1997 dependent resurvey executed under Group No. 771.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>SC</p> <p>T20S R54E</p> <p>S33 S34</p> <hr style="width: 50px; margin: 0 auto;"/> <p>2010</p> </div> <p>Insert the rebar inside the stainless steel post.</p> <hr/> <p style="text-align: center;">DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 20 S., R. 54 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p style="text-align: center;">Reestablishment of the Survey Executed by U.S. Deputy Surveyor T. Binge in 1881</p> <hr/> <p>From the standard cor. of secs. 34 and 35, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 3°09'50" E., bet. secs. 34 and 35.</p> <p>Over gently rolling land, through creosote and scattered cacti.</p> <p>Power transmission line, bears S. 67° E. and N. 67° W.</p> <p>The 1/4 sec. cor. of secs. 34 and 35, monumented with a rebar, 5/8 in. diam., firmly set, projecting 2 ins. above the center of an eroded mound of earth, with aluminum cap mkd. VTN ENGR RLS 2050, no map record found, with a limestone, 9x9x6 ins. (record, granite, 18x9x7 ins.), mkd. 1/4 on one side, laying alongside the rebar. This is accepted as a careful and faithful perpetuation of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T20S R54E</p> <p>1/4</p> <p>S34 S35</p> <hr style="width: 50px; margin: 0 auto;"/> <p>2010</p> </div>
---	---