

SUBDIVISION OF SECTION 28,  
T. 33 N., R. 33 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>From the point for the 1/4 sec. cor. of secs. 28 and 33. N. 0°06'20" E., on the N-S center line of sec. 28. Across Rye Patch Reservoir.</p>
40.105	<p>Point for the center 1/4 sec. cor. of sec. 28, at intersection with the E-W center line, falls in Rye Patch Reservoir; no permanent monument established.</p>
59.305	<p>Point for the C-N 1/16 sec. cor. of sec. 28, falls in Rye Patch Reservoir; no permanent monument established.</p>
59.80	<p>Waters edge, Rye Patch Reservoir, bears SE. and NW.; enter nearly level land, through medium growth of shadscale and bud-sage.</p>
60.631	<p>Point for a witness point, at intersection with the 4144 foot contour line, on the north side of Rye Patch Reservoir.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div data-bbox="824 898 1031 1144" style="text-align: center;"> <p>WP T33N R33E C 4144 FT   S28 C 2010</p> </div>
70.60	<p>Jeep trail, 20 lks. wide, bears SE. and NW.</p>
78.505	<p>The 1/4 sec. cor. of secs. 21 and 28.</p>
	<hr/> <p>From the 1/4 sec. cor. of secs. 27 and 28, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 12 ins. above the ground, and in a mound of stone, 3 ft. base, 8 ins. high, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 33 N., R. 33 E., executed under Group No. 498, with a steel fence post set alongside.  N. 89°01'40" W., on the E-W center line of sec. 28.  Over gently rolling land, through medium growth of shadscale, bud-sage and greasewood.</p>
4.985	<p>Point for a witness point, at intersection with the 4144 foot contour line, on the north side of Rye Patch Reservoir.  Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>