## DEPENDENT RESURVEY OF THE FIRST STANDARD PARALLEL SOUTH THROUGH A PORTION OF RANGE 70 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

Reestablishment of a Portion of the Survey
Executed by U.S. Deputy Surveyor H.B. Maxson in 1901,
and a Portion of the Dependent Resurvey
Executed by U.S. Deputy Surveyor C.F. Moore in 1922

Beginning at the standard cor. of secs. 34 and 35, determined at a basalt stone,  $18 \times 9 \times 7$  ins., mkd. with 4 grooves on one face, 2 grooves on one face and SC on one face, lying loose on the ground.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.

SC T4S R70E S34 S35

2008

Bury basalt stone alongside stainless steel post.

From this corner, the standard 1/4 sec. cor. of sec. 34, bears N.  $89^{\circ}44'20"$  W., 39.834 chs. dist., monumented with a basalt stone, 15x9x7 ins., firmly set, projecting 5 ins. above the ground, mkd. 1/4 on the N. face, from which the original bearing trees

A cedar, 17 ins. diam., bears N. 39  $1/2^{\circ}$  E., 42 lks. dist., mkd. 1/4 S34 BT on an open blaze.

A cedar, 12 ins. diam., bears N. 61  $1/4^{\circ}$  W., 120 lks. dist., mkd. 1/4 S34 BT on an open blaze.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd.

SC T4S R70E 1/4 S34

2008

Bury basalt stone alongside stainless steel post.

S.  $89^{\circ}53'50"$  E., on the S. bdy. of sec. 35.

Over nearly level land, through scattered pinon pine and juniper.

39.947

Point for the standard  $1/4~{\rm sec.}$  cor. of sec. 35, at proportionate distance; there is no remaining evidence of the original corner.