

DEPENDENT RESURVEY OF THE FIRST STANDARD PARALLEL SOUTH
THROUGH A PORTION OF RANGE 70 EAST,
MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
39.430	<p>The standard cor. of Tps. 4 S., Rs. 70 and 71 E., monumented with a granite stone, 12x10 ins., firmly set, projecting 5 ins. above the ground, mkd. with 6 grooves on the N. and W. faces, 3 grooves on the E. face, and SC on the N. face, alongside of which is an iron post, 3 ins. diam., firmly set, projecting 6 ins. above the ground, and in a mound of stone, 3 ft. base, 1 ft. high, with brass cap mkd. as described in the field notes of the dependent resurvey executed in 1922 under Group No. 95, from which the original bearing trees</p>
	<p>A cedar, 14 ins. diam., bears N. 40 3/4° E., 71 lks. dist., mkd. T4S R71E S31 BT on an open blaze.</p>
	<p>A cedar, 12 ins. diam., bears N. 26° W., 71 lks. dist., mkd. T4S R70E S36 BT on an open blaze.</p>
	<hr/> <p>DEPENDENT RESURVEY OF PORTIONS OF THE EAST BOUNDARY, T. 5 S., R. 70 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/>
	<p>Reestablishment of a Portion of the Survey Executed by U.S. Deputy Surveyor H.B. Maxson in 1901, and a Portion of the Dependent Resurvey Executed by U.S. Deputy Surveyor C.F. Moore in 1922</p> <hr/>
	<p>From the cor. of secs. 12 and 13 only, monumented with a basalt stone, 8x4 ins., firmly set, projecting 7 ins. above the ground, alongside of which is an iron post, 2 ins. diam., firmly set, projecting 9 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey executed in 1922 under Group No. 95, from which the remaining original bearing trees</p>
	<p>A cedar, 10 ins. diam., bears S. 45 1/2° W., 90 lks. dist., mkd. T5S R70E S13 BT on an open blaze.</p>
	<p>A cedar, 10 ins. diam., bears N. 86 1/2° W., 262 lks. dist., mkd. T5S R70E S12 BT on an open blaze.</p>
	<p>N. 0°16'40" W., on the E. bdy. of sec. 12.</p>
	<p>Over nearly level land, through pinon pine and juniper.</p>
0.518	<p>The cor. of secs. 7 and 18 only, T. 5 S., R. 71 E., monumented with an iron post, 2 ins. diam., firmly set, projecting 9 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey executed in 1922 under Group No. 95, from which the 1922 bearing trees</p>
	<p>A cedar, 8 ins. diam., bears N. 37 1/4° E., 47 lks. dist., mkd. T5S R71E S7 BT on an open blaze.</p>
	<p>A cedar, 15 ins. diam., bears S. 21 1/2° E., 119 lks. dist., mkd. T5S R71E S18 BT on an open blaze.</p>
10.00	<p>Low ridge, bears NW. and SE.</p>
20.192	<p>Point for the S 1/16 sec. cor. on the E. bdy. of sec. 12.</p>