

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES  
T. 5 S., R. 71 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Beginning at the 1/4 sec. cor. of secs. 7 and 8, monumented with an iron post, 1 in. diam., firmly set, 6 ins. below the surface of ground, with brass cap mkd. as described in the field notes of the survey executed in 1922 under Group No. 95, from which the original bearing trees</p> <p style="padding-left: 40px;">A cedar, 18 ins. diam., bears S. 81 1/2° E., 100 lks. dist., mkd. 1/4 S8 BT on an open blaze. (Record, 177 lks. dist.)</p> <p style="padding-left: 40px;">A cedar, 10 ins. diam., bears N. 84 1/4° W., 177 lks. dist., mkd. 1/4 S7 BT on an open blaze. (Record, 100 lks. dist.)</p> <p>N. 0°14'40" W., bet. secs. 7 and 8.</p> <p>Ascend through pinon pine and juniper.</p> <p>2.40 Spur, slopes SE.</p> <p>11.00 Draw, drains E.</p> <p>21.30 Old Beaver Dam Road, 18 lks. wide, bears SSE. and NNW.</p> <p>21.45 Northerly edge of Old Beaver Dam Road, bears SSE. and NNW.</p> <p>23.951 The witness point, at the intersection of the first course of a metes-and-bounds survey with the line bet. secs. 7 and 8, hereinafter described.</p> <p>26.10 Top of cliff, face bears E. and W.</p> <p>28.70 Spur, slopes SE.</p> <p>39.920 The cor. of secs. 5, 6, 7 and 8, monumented with an iron post, 2 ins. diam., firmly set, in a mound of stone, 4 ft. base, 2 1/2 ft. high, with brass cap mkd. as described in the field notes of the survey executed in 1922 under Group No. 95, from which the original bearing trees</p> <p style="padding-left: 40px;">A pinon pine, 10 ins. diam., bears N. 35 1/2° E., 41 lks. dist., mkd. T5S R71E S5 BT on an open blaze.</p> <p style="padding-left: 40px;">A cedar, 18 ins. diam., bears S. 37 1/4° E., 16 lks. dist., mkd. T5S R71E S8 BT visible on an open blaze.</p> <p style="padding-left: 40px;">A pinon pine, 11 ins. diam., bears S. 48 1/4° W., 153 lks. dist., mkd. T5S R71E S7 BT on an open blaze.</p> <p style="padding-left: 40px;">A pinon pine, 12 ins. diam., bears N. 66 1/2° W., 40 lks. dist., mkd. T5S R71E S6 BT on an open blaze.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 6 and 7, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above the ground, with brass cap mkd. as described in the field notes of the survey executed in 1922 under Group No. 95, from which the original bearing trees</p> <p style="padding-left: 40px;">A pinon pine, 10 ins. diam., bears N. 51 1/2° E., 155 lks. dist., mkd. 1/4 S6 BT on an open blaze.</p>
--------	---