

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,  
T. 14 S., R. 69 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p style="text-align: center;">Reestablishment of a Portion of the Independent Resurvey Executed by Cadastral Surveyor R.A. Zaninovich in 2000</p> <hr/> <p>Beginning at the cor. of secs. 1, 6, 7 and 12, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of the independent resurvey of T. 14 S., R. 69 E., executed under Group No. 789, with a steel fence post set alongside.</p> <p>North, bet. secs. 1 and 6.</p> <p>21.413 Point for Angle Point No. 8, sec. 6, hereinafter described.</p> <p>40.000 The 1/4 sec. cor. of secs. 1 and 6, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of the independent resurvey of T. 14 S., R. 69 E., executed under Group No. 789, with a steel fence post set alongside.</p> <hr/> <p>North, beginning new measurement.</p> <p>21.580 Point for Angle Point No. 9, sec. 6, hereinafter described.</p> <p>40.000 The cor. of secs. 1, 6, 31 and 36, Tps. 13 and 14 S., Rs. 68 and 69 E., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of the independent resurvey of T. 14 S., R. 69 E., executed under Group No. 789, with a mound of stone, 3 ft. base, 18 ins. high, S. of cor.</p> <hr/> <p style="text-align: center;">DEPENDENT RESURVEY OF PORTIONS OF THE NORTH BOUNDARY, T. 14 S., R. 69 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p style="text-align: center;">Reestablishment of a Portion of the Independent Resurvey Executed by Cadastral Surveyor R.A. Zaninovich in 2000</p> <hr/> <p>From the cor. of secs. 4, 5, 32 and 33, monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above the ground, and in a mound of stone, 5 ft. base, to top, with brass cap mkd. as described in the field notes of the independent resurvey of T. 14 S., R. 69 E., executed under Group No. 789.</p> <p>From this cor., the center of an FAA VORTAC building, located in the SE1/4SE1/4 of sec. 28, T. 13 S., R. 69 E., bears N. 35°13'50" E., 108.05 chs. dist.</p> <p>From this same cor., the cor. of secs. 27, 28, 33 and 34, T. 13 S., R. 69 E., bears N. 45°07'00" E., 112.83 chs. dist., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above the ground, and in a collar of stone, with brass cap mkd. as described in the field notes of the independent resurvey of T. 13 S., R. 69 E., executed under Group No. 789.</p>
--------	---