## DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY T. 15 S., R. 67 E., MOUNT DIABLO MERIDIAN, NEVADA

T. 15 S., R. 67 E., MOUNT DIABLO MERIDIAN, NEVADA	
CHAINS	Reestablishment of a Portion of the Survey Executed by R.H. Woods and W.H. Myrick, U.S. Deputy Surveyors, in 1881
	Beginning at the cor. of secs. 13, 18, 19 and 24, monumented with a sandstone, 8x6x6 ins. (Record, limestone, 10x10x6 ins.), firmly set, projecting 4 ins. above the ground, plainly mkd. with 3 grooves on S. face and 3 grooves on N. face, in a mound of stone, 3 ft. base, 1 ft. high.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	T15S R66E R67E S13 S18
	S24 S19
	2008
	Bury the mkd. stone alongside the stainless steel post and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
	Cor. is located on a spur, slopes N.
	N. 0°03'10" E., bet. secs. 13 and 18.
	Over broken land.
5.30	Dry wash, 200 lks. wide, drains NE.
38.50	Dry wash, 30 lks. wide, drains NE.
40.128	The 1/4 sec. cor. of secs. 13 and 18, monumented with a sandstone, 17x12x11 ins. (Record, granite, 10x8x6 ins.), firmly set in a mound of stone, 3 ft. base, 6 ins. high, plainly mkd. 1/4 on the E. face.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, over a plastic-encased magnet and in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	T15S 1/4 R66E R67E S13 S18
	2008
	Bury the mkd. stone alongside the stainless steel post.