DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 15 S., R. 67 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	
	T15S R67E 1/4 S 6|S 5 2009
	from which
	A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears S. 10°50' E., 87.0 lks. dist., with brass cap mkd. RM 1/4 S5 57.4 FT TO COR 2009 and an arrow pointing to corner.
	A brass tablet, 3 1/4 ins. diam., 3 1/2-in. stem, cemented flush in drill hole in a limestone boulder, for a reference monument, bears S. 37°07' W., 79.2 lks. dist., mkd. RM 1/4 S6 52.3 FT TO COR 2009 and an arrow pointing to the corner.
	Cor. is located in powerline road, 20 lks. wide, bears SE. and NW.
79.818	The cor. of secs. 5, 6, 31 and 32, on the N. bdy. of the Tp. hereinbefore described.
	SUBDIVISION OF SECTION 7, T. 15 S., R. 67 E., MOUNT DIABLO MERIDIAN, NEVADA
	From the 1/4 sec. cor. of secs. 7 and 18.
	N. 0°25'30" E., on the N-S centerline of sec. 7.
	Over steep and rocky ridges.
20.002	The C-S 1/16 sec. cor. of sec. 7, determined by R. Guy Doty, Nevada Professional Land Surveyor No. 7635, monumented with a rebar, 5/8 in. diam., 18 ins. long, firmly set flush with the surface of the ground, with aluminum cap, 1 1/2 ins. diam., mkd. R GUY DOTY PLS 7635, as recorded in Clark County, Nevada, File 147, Page 26 of Surveys, and is accepted as a careful and faithful determination of the position of the corner.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	C S 1/16 | S 7 C 2009
	Bury the rebar alongside the stainless steel post.