

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 12 N., R. 30 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Beginning at the cor. of secs. 35 and 36, on the S. bdy. of the Tp., monumented with an iron post, 2 ins. diam., firmly set in a mound of stone, 4 ft. base, 2 ft. high, to top, with brass cap mkd. as described in the field notes of the survey of T. 12 N., R. 30 E., executed under Group No. 181.</p> <p>N. 0°02'50" W., bet. secs. 35 and 36.</p> <p>Over rolling land, with low brush.</p>
40.000	<p>Point for the 1/4 sec. cor. of secs. 35 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, to bedrock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T12N R30E 1/4 S35 S36 2010</p> </div>
48.70	<p>Wash, 38 lks. wide, drains S. 76° E.</p>
80.000	<p>Point for the cor. of secs. 25, 26, 35, and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T12N R30E S26 S25 S35 S36 2010</p> </div> <hr/> <p>From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set in a mound of stone, 4 ft. base, 2 ft. high, with brass cap mkd. as described in the field notes of the survey of T. 12 N., R. 31 E., executed under Group No. 865.</p> <p>S. 89°59'30" W., bet. secs. 25 and 36.</p> <p>Over rolling land, with medium undergrowth.</p>
38.50	<p>Ridge, bears N. 43° W. and S. 40° E.</p>
39.977	<p>Point for the 1/4 sec. cor. of secs. 25 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, to bedrock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p>