

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 13 N., R. 31 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>Beginning at the cor. of secs. 4, 5, 32 and 33, on the S. bdy. of the Tp., monumented with a stainless steel post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of the survey of T. 12 N., R. 31 E., executed under Group No. 865.</p> <p>N. 0°02'50" W., bet. secs. 32 and 33.</p> <p>Over gently rolling land, with sagebrush and shadscale.</p>
29.00	Enter shallow wash, drains N. 38° W.
32.40	Leave shallow wash.
40.000	<p>Point for the 1/4 sec. cor. of secs. 32 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T13N R31E 1/4 S32 S33 2010</p> </div>
54.80	Enter dry lake bed.
67.50	Leave dry lake bed.
80.000	<p>Point for the cor. of secs. 28, 29, 32 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> <p>T13N R31E S29 S28 ----- S32 S33 2010</p> </div>
40.012	<p>From the cor. of secs. 27, 28, 33 and 34, monumented with an iron post, 2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd. as described in the field notes of the survey of T. 13 N., R. 31 E., executed under Group No. 181, and additionally mkd. WRIR on W. side of cap, with a mound of stone, 2 ft. base, 1 ft. high, W. of cor.</p> <p>N. 89°56'20" W., bet. secs. 28 and 33.</p> <p>Descend over gently rolling land, with sagebrush and shadscale.</p> <p>Point for the 1/4 sec. cor. of secs. 28 and 33.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p>