

DEPENDENT RESURVEY OF THE FOURTH STANDARD PARALLEL SOUTH,
THROUGH A PORTION OF RANGE 49 EAST,
MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	S. 89°55'40" W., beginning new measurement.
13.903	<p>The westerly angle point on the S. bdy. of sec. 33, monumented with the rusted remains of the base of an iron post, 2 ins. diam., firmly set 30 ins. below the surface of the ground.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 12 ins. below the surface of the ground, over a plastic-encased magnet, with brass cap mkd.</p> <div style="text-align: center;"> AP T16S R49E S33 <hr style="width: 10%; margin: 0 auto;"/> 2010 </div> <p>from which I add</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears N. 45°01' E., 68.2 lks. dist., with brass cap mkd. RM T16S R49E AP S33 45.0 FT. TO COR. 2010 and an arrow pointing to the corner.</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground, for a reference monument, bears S. 45°01' E., 68.2 lks. dist., with brass cap mkd. RM T17S R49E AP S5 45.0 FT. TO COR. 2010 and an arrow pointing to the corner.</p> <p>Bury the remains of iron post alongside the stainless steel post.</p> <hr/> <p style="text-align: center;">DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T.17 S., R.49 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>From the cor. of secs. 2, 3, 10 and 11, reestablished by Russell Avery, Nevada Professional Land Surveyor No. 2002, as recorded in Nye County, Nevada, Record of Survey, Document No. 50519, and subsequently reestablished by Lisle Lowe, Nevada Professional Land Surveyor No. 8423, as recorded in Nye County, Nevada, Document No. 369296, monumented with a rebar, 1/2 in. diam., firmly set 12 ins. below ground, no cap found, and is accepted as a careful and faithful reestablishment of the position of the original corner.</p> <p>from which I add</p> <p>A stainless steel post, 28 ins. long, 2 1/2 ins. diam., set 27 ins. in the ground, over a plastic-encased magnet, for a reference monument, bears N. 45°08' E., 151.5 lks. dist., with brass cap mkd. RM T17S R49E S2 100.0 FT. TO COR. 2010 and an arrow pointing to the corner.</p>