

DEPENDENT SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T 17 S., R. 49 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	<p>651279, and is accepted as a careful and faithful reestablishment of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., flush with the surface of the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T17S R49E 1/4 S 5 S 4</p> <p style="text-align: center;">2010</p> <p>Deposit the rebar inside the stainless steel post.</p> <hr/> <p>N. 2°20'10" W., beginning new measurement.</p> <p>Continue over nearly level land, along E. side of Windjammer Road.</p>
38.090	<p>The closing cor. of secs. 4 and 5, on the Fourth Standard Parallel South, hereinbefore described.</p> <hr/> <p style="text-align: center;">SUBDIVISION OF SECTION 3, T. 17 S., R. 49 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>From the 1/4 sec. cor. of secs. 3 and 10.</p> <p>N. 2°10'00" W., on the N-S center line of sec. 3.</p> <p>Over nearly level land, through sagebrush and creosote brush.</p>
0.20	<p>Center of Mecca Road, asphalt surfaced, 36 lks. wide, bears E. and W.</p>
0.60	<p>Power transmission line, bears E. and W.</p>
37.554	<p>The center 1/4 sec. cor. of sec. 3, monumented with an unrecorded rebar, 1/2 in. diam., firmly set flush with the surface of the ground, with plastic cap mkd. PLS 6444, and is accepted as a careful and faithful determination of the position of the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.</p> <p style="text-align: center;">T17S R49E C 1/4 S 3</p> <p style="text-align: center;">2010</p>