

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 8 S., R. 61 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Reestablishment of a Portion of the Survey Executed by U.S. Deputy Surveyor E.B. Monroe in 1870
	<p>From the standard cor. of secs. 35 and 36, on the S. bdy. of the Tp., hereinbefore described.</p> <p>N. 0°32'50" E., bet. secs. 35 and 36.</p> <p>Over gently rolling land, through scattered undergrowth.</p>
1.00	Draw, drains E.
12.40	Draw, drains S. 80° E.
27.40	Draw, drains N. 40° E.
35.00	Spur, bears S. 60° E. and N. 60° W.
39.018	<p>The 1/4 sec. cor. of secs. 35 and 36, monumented with a trachyte stone, 22x9x7 ins., firmly set, projecting 16 ins. above an embedded mound of stone, 3 ft. base, 6 ins. high, plainly mkd. 1/4 on W. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T8S R61E 1/4 S35 S36</p> <p style="text-align: center;">2010</p> <p>Bury the mkd. stone alongside the stainless steel post.</p> <p>Corner is located in a deep draw, drains S. 65° E.</p>
	<p>N. 0°07'20" E., beginning new measurement.</p> <p>Over gently rolling land, through scattered undergrowth.</p>
9.10	Spur, bears S. 40° E. and N. 40° W.
27.50	Draw, drains S. 65° E.
35.00	Spur, bears S. 60° E. and N. 60° W.
38.748	<p>The cor. of secs. 25, 26, 35 and 36, monumented with a trachyte stone, 20x8x6 ins., firmly set, projecting 10 ins. above a mound of stone, 3 ft. base, 1 ft. high, plainly mkd. with 1 notch on the E. edge and 1 notch on the S. edge.</p> <p>At the corner point</p>