SUBDIVISION OF SECTION 24, T. 8 S., R. 61 E., MOUNT DIABLO MERIDIAN, NEVADA

	1. 0 S., R. 01 E., MOUNT DIABLO MERIDIAN, NEVADA
CHAINS	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a plastic-encased magnet, and in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.
	S24
	C-W-NW
	1/64
	2010
	Set a steel fence post alongside the stainless steel post.
17.40	Improved gravel road, 30 lks. wide, bears S. 20° E. and N. 20° W.
18.20	Enter bottom lands, edge bears S. 10° W. and N. 20° W.; through grasses.
20.166	The point for the N 1/16 sec. cor. of secs. 23 and 24.
	From the C-W-NW 1/64 sec. cor. of sec. 24.
	N. 1°00'30" E., on the N-S center line of the NW1/4 of the NW1/4 of sec. 24.
	Over gently rolling land, through scattered undergrowth.
7.20	U.S. Highway No. 93, asphalt surfaced, 45 lks. wide, bears S. 20° E. and N. 20° W.
20.261	The W-W 1/64 sec. cor. of secs. 13 and 24.
	SUBDIVISION OF SECTION 25, T. 8 S., R. 61 E., MOUNT DIABLO MERIDIAN, NEVADA
	From the 1/4 sec. cor. of secs. 25 and 36.
	N. 0°34'40" E., on the N-S center line of sec. 25.
	Over bottom lands, through grasses and tulles.
12.50	Ravine, drains N. 30° E.
20.000	The C-S 1/16 sec. cor. of sec. 25, determined by the Bureau of Sport Fisheries and Wildlife, as shown on an unrecorded plat entitled "PAHRANAGAT NWR", surveyed August, 1963, monumented with a concrete post, 3 ins. diam., 18 ins. long, firmly set flush with the top of a mound of stone, 2 1/2 ft. base, with a standard brass tablet, firmly cemented to the top of the concrete post, mkd. BUREAU OF SPORT FISHERIES AND WILDLIFE C S1/16 S25 1963, with a steel fence post set alongside. This is accepted as a careful and faithful determination of the position of the corner.
	At the corner point