DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY, T. 31 N., R. 33 E., MOUNT DIABLO MERIDIAN, NEVADA

	T. 31 N., R. 33 E., MOUNT DIABLO MERIDIAN, NEVADA
CHAINS	
46.20	Barbed wire fence, parallel with railroad tracks, bears SSW., and NNE. for 15 lks. dist., to a corner of barbed wire fences extending NNE., SSW. and W.
59.886	Point for the W $1/16$ sec. cor. of secs. 5 and 32.
	Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, over a plastic-encased magnet, with brass cap mkd.
	W 1/16 = S32 S 5
	2010
79.848	The cor. of secs. 5, 6, 31 and 32, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the N. bdy., T. 30 N., R. 33 E., executed under Group No. 523, with a wood post, 6x8 ins. diam., projecting 3 ft. above the ground, N. of cor.
	DEPENDENT RESURVEY OF THE WEST BOUNDARY, T. 31 N., R. 33 E., MOUNT DIABLO MERIDIAN, NEVADA
	Reestablishment of the Survey Executed by U.S. Deputy Surveyor E.H. Dyer in 1863
	From the cor. of Tps. 30 and 31 N., Rs. 32 and 33 E., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the W. bdy., T. 30 N., R. 33 E., executed under Group No. 523, with a steel fence post set alongside.
	N. 0°33'30" W., bet. secs. 31 and 36.
	Across broken land, covered with shadescale, low brush and grasses.
41.324	The 1/4 sec. cor. of secs. 31 and 36, perpetuated by John H. Milton III, Nevada Professional Land Surveyor No. 5271, monumented with a rebar, 5/8 in. diam., projecting 5 ins. above the ground, with damaged plastic cap, marks illegible, with a steel fence post set alongside, as recorded in the Office of the Recorder, Pershing County, Nevada, Map No. P-292, File No. 228025, and is accepted as a careful and faithful perpetuation of the position of the original corner.